

Compactors

Apartment Compactor

C-TEC's apartment compactor gives big service in a small area. Available for chute or ground loading and packs into a front load or rear load receiver container. Requires less than 12.5' in length for both compactor and container. UL approved and ANSI compliant.



Model: AP 001



UL Listed

COMPACTOR SPECIFICATIONS

MFG Rating CU/YD	0.39
Wastec Rating CU/YD	0.33
Clear Top Opening (L" x W")	21" x 31 1/8"
Ram Face (H" x W')	19 7/8' x 30 7/8'
Ground height	8"
Capacity per Hour	70

PERFORMANCE

Cycle Time (Seconds)	15
Normal Force lbs.	14.432
Maximum Force lbs.	16.906
Normal Ram face Pressure PSI	24.1
Maximum Ram Face Pressure PSI	28.2
Ram Penetration	6"

HYDRAULIC / ELECTRICAL

Motor HP	5
Control Voltage	120 VAC
Pump GPM	5.2
Normal System Pressure PSI	1,700
Maximum System Pressure PSI	2,000
Cylinder Bore / Rod Diameter	4" / 2"
Stroke	24"
Single Cylinder	Yes
Hydraulic Tank-Capacity gallons	7

CONSTRUCTION

Charge Box Sides	1/4"
Exterior Vertical / Horizontal Formed V	No
Charge Box Floor	3/8"
Ram Face	1/2"
Ram Bottom	1/4"
Ram Top	1/4"
Breaker Bar Structural angle	3.5" x 3.5" x 1/2"
Weight	1,400
Other	Double Side Release

CONTAINER SPECIFICATIONS

	Rear Load
Overall Length	77 1/2"
Overall Width	41 1/2"
Overall Height	58" Ref*
Capacity	2 cu. yds.
Weight	670 lbs.
Sides	10 gauge
Floor	10 gauge
Lids	14 gauge
Pockets	-
Trunnion Bar	1 1/2" dia.
Pocket Height	-
Trunnion Bar Height	48" (to top)
Trunnion Bar Length	77 1/2" (or specify)
Swivel Casters	(2) - 6" Polyurethane / Steel
Rigid Casters	(2) - 6" Polyurethane / Steel
Charge Door Opening	33" W x 26" H

**C-TEC's Apartment Compactor
is big on performance.**